

Packaged Terminal Air Conditioner for Replacement

# RSAN Series

ICE AIRs RSAN Series New Construction and Replacement units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

**Features:**

- Ultra-high efficiency – EERs to 11.9
- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry


**Replaces:**

McQuay – PDNS, PGAN, N, NH  
 Singer – N, NH  
 Islandaire – N, NH, NE

MODEL		5RSAN07	5RSAN09	5RSAN13	8RSAN07	8RSAN09	8RSAN13	8RSAN15	8RSAN18
Cooling	Capacity*	7,500	9,600	12,200	7,500	9,600	12,700	15,000	16,600
	EER	11.9	11.2	11.2	11.9	11.2	11.2	10.1	9.5
Heating Capacity	Hot Water**	17,200	17,200	17,200	17,200	17,200	17,200	19,500	19,500
	Steam***	18,700	18,700	18,700	18,700	18,700	18,700	20,200	20,200
Electric Heating. Max.		1.5	1.5	3.0	1.5	1.5	3.0	3.0	3.0
Voltage		115	115	115	208/230	208/230	208/230	208/230	208/230
Amperage		5.5	7.5	10.3	3.0	4.1	6.0	7.1	8.6
Watts		630	857	1,089	630	857	1,134	1,485	1,747
CFM Room	Air High	350	400	450	350	400	450	475	450
	Air Low	245	280	315	245	280	315	333	370
	Heat High	245	280	315	245	280	315	333	N/A
	Heat Low	210	210	210	210	210	210	210	220
CFM Outside Air		60	60	60	60	60	60	60	60
CFM X Outside Air		110	110	110	110	110	110	110	110
Weight Net/Ship		113/129	117/133	117/133	113/129	117/133	117/133	132/148	141/157

**Specification Notes:**

\* BTUH @ 80°F DB/67°F. WB indoors; 95°F. DB outdoors.

\*\* BTUH @ 200°F E.W.T.; 65°F. E.A.T. & 2 G.P.M. Flow rate

\*\*\* BTUH @ 2 PSIG Steam & 65°F. E.A.T.