

Packaged Terminal Air Conditioner for Replacement

RSCC Series

ICE AIRs RSCC Series

Replacement and Retrofit units are high energy efficiency PTACs. Designed from the ground up for ultra-high efficiency, they incorporate advanced LEEDs features in a durable and user-friendly package.

Features:

- Advanced tangential indoor blower provides balanced air flow
- Whisper quiet sound levels
- Standard programmable digital touchpad controls
- 5/2 or 7 day programming
- Heavy duty, commercial-grade construction throughout
- G90 galvanized steel construction, powder-coated drain and base pans
- Furniture-grade, powder-coated cabinetry



RSCC Replaces:

Ice-Cap – RSCT
 Ice Air – RSET

MODEL	5RSCC07	5RSCC09	5RSCC13	8RSCC09	8RSCC13	8RSCC16	8RSCC18	7RSCC09	7RSCC13	7RSCC18
Nominal Cooling Cap. (1)	8,100	9,500	12,750	9,700	12,700	14,400	16,200	9,250	12,500	16,200
Cooling EER	9.5	8.8	8.3	8.7	8.3	8.3	7.7	8.7	8.3	7.7
Heating Capacity HW (2)	16,500	16,500	16,500	16,500	16,500	19,400	19,400	16,500	16,500	19,400
Heating Capacity STM (3)	18,700	18,700	18,700	18,700	18,700	20,000	20,000	18,700	18,700	20,000
Electric Heat Cap. (KW)	1.5	1.5	1.5	1.5	3.5/4.3	3.5/4.3	3.5/4.3	1.5	3.5/4.3	3.5/4.3
Voltage	115	115	115	208	208	208	208	277	277	277
Amperage	6.5	7.9	11.0	4.2	6.8	7.4	9.1	3.4	4.8	6.6
Watts	853	1,080	1,536	1,115	1,530	1,735	2,104	1,063	1,506	2,104
CFM Air Hi Cool	370	370	370	370	430	430	480	370	430	480
CFM Air Lo Cool	260	260	260	260	330	330	330	260	330	330
CFM Outside Air	60	60	60	60	60	60	60	60	60	60
CFM Extra Outside Air	110	110	110	110	110	110	110	110	110	110
Weight - Net/Ship	113/129	117/133	124/138	113/129	124/138	132/148	141/157	117/133	124/138	141/157

Notes:

1. Btu/h @ 80°F DB/67°F WB Indoors/95°F DB Outdoors
2. Btu/h @ 200°F E.W.T./65°F E.A.T./2 GPM Flow Rate
3. Btu/h @ 2 P.S.I.G. Steam/65°F E.A.T.
4. For heat pump performance, contact ICE AIR directly